

FUZZYSCAN F780 Series

cino®


A Ruggedized, High Performance Bar Code Linear Imager for Industry and General Purpose Applications



Thanks to the revolutionary FuzzyScan 2.0 Imaging Technology and ruggedized construction, the new FuzzyScan F780 bar code linear imager from Cino impresses the user with high scanning performance and exceptional reliability. The F780 series is the best-of-breed blend of form and functionality to meet the need of industry and general purpose applications.

Compact yet ruggedized construction

To deliver the highest level of dependability, the F780 is built with compact and robust over-mold housing. It is rugged enough to withstand multiple drops from 1.6 meter to concrete to meet your day-to-day scan-intensive use.



Outstanding reading performance

The F780 provides outstanding performance on reading damaged, smudged, poorly-printed and low contrast barcode labels that are commonly found in the real world quickly and accurately.

Latest linear-stacked barcodes support

To meet the latest application requirement, the F780 supports most popular linear-stacked barcodes, including PDF, MicroPDF, Codablock, GS1 Databar Linear-stacked and Composite.



Ruggedized over-mold design to withstand multiple drops to concrete from 1.6 meter

GS1 DataBar, PDF, MicroPDF and composite code support

Outstanding reading capability on 3 mil barcode with more than 2" depth of field

More than 16" reading distance on 100% UPC/EAN symbols

Unsurpassed readability on low contrast, smudged, poorly-printed or damaged barcodes

Superior motion tolerance for rapid and accurate data-capture on the move

High speed scanning rate up to 500 scans per second for snappy barcode capture

All-in-one host interface design, including USB HID, USB COM, PS/2 keyboard wedge and RS232

Automatically switch between presentation scanning and hand-held scanning while working with Cino SmartStand

Optional vibrator for noisy working environment

Athesi
Mobile Generation

www.athesi.com

cino®

FUZZYSCAN
www.cino.com.tw

Specifications

Performance Characteristics

| | |
|-------------------------------|--|
| Optical System | High performance Linear Imaging Engine |
| Print Contrast | 20% minimum reflective difference |
| Minimum Resolution | Typical 3 mil (Code 39, PCS 0.9) |
| Working Distance ¹ | More than 16 inches on 100% UPC/EAN symbols More than 24 inches on 20 mil Code 39 |
| Light Source | 630nm visible red LED |
| Scan Rate | Dynamic scanning rate up to 500 scans per second |
| Reading Direction | Bi-directional (forward and backward) |
| Pitch/Skew | ± 65' ± 65" |
| Operating Modes | Toggle, Trigger, Force, Level, Flash, Diagnostic Alternative, Low power, Presentation |
| Host Interfaces | PC/AT, PS/2 (DOS V) keyboard wedge PC/AT, PS/2 (DOS V) keyboard direct link TTL RS232 serial USB HID (USB Keyboard) USB COM port emulation Laser emulation and Wand emulation |
| Configuration Setup | Bar code command Windows utility - FuzzyScan PowerTool |
| Data Editing | Condensed DataWizard via bar code command Full-feature DataWizard via FuzzyScan PowerTool |
| User Interfaces | 3 LEDs for power, good read and status indications Programmable beeper Optional vibrator |

Supported Symbolologies

| | |
|-----------------------|--|
| 1D Linear (F780) | Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic Code 128, UCC/EAN-128, Codabar, Code 11, Code 93 Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5 German Postal Code, China Postal Code, IATA UPC/EAN/JAN, UPC/EAN/JAN with Addendum Telepen, MSI/Plessey & UK/Plessey GS1 DataBar (formly RSS) Linear, Linear-stacked |
| Linear-stacked (F788) | PDF417, Micro PDF417, Codablock, Composite |

User Environment

| | |
|------------------------|--|
| Drop Specifications | Withstand multiple 1.6m/5ft. drops to concrete |
| Environmental Sealing | IP41 |
| Operating Temperature | 0°C to 50°C (14°F to 122°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158°F) |
| Humidity | 5% to 95% related humidity, non-condensing |
| Ambient Light Immunity | ~ 100,000 lux |
| ESD Protection | Functional after 15kV discharge |

1. The working distances are measured in 400lux office environment using Grade A bar codes.
2. Don't stare into the LED beam.

Physical Characteristics

| | |
|---------------|--|
| Dimension | 97.8 mm (L) x 70.5 mm (W) x 156.2 mm (D) 3.85 in. (L) x 2.77 in. (W) x 6.15 in. (D) |
| Weight | 157g (cable excluded) |
| Color | Light Gray or Black |
| Input Voltage | 5VDC ± 10% |
| Current | Operating : Typical 180 mA @5VDC Standby : Typical 80 mA @5VDC |


Safety & Regulatory

| | |
|---------------------|---|
| EMI/RFI | FCC Part 15 Class B, ICES-003 Class B European Union EMC Directive (CE) Taiwan EMC (BSMI) |
| Safety ² | LED Eye Safety IEC60825-1, EN60825-1 |
| Environmental | Compliant with RoHS directive |

Accessories

| | |
|--------|---|
| Cables | PS/2 (DOS V) Keyboard Wedge Cable RS232 Serial Cable USB Cable USB Power Steal Cable |
| Others | Hand-free SmartStand Universal Holder |

Accessories



Colors Available ■ black ■ light gray

Athesi
Mobile Generation

Imported by ATHESI - 13 Villa Languedoc 94430 - Chennevières Sur Marne FRANCE
Tél. +33 (0)1 74 01 71 21 - Fax +33 (0)1 74 01 71 28 - Email info@athesi.com - www.athesi.com

Part number :YMAUG00030020R0. ©Copyright PC Worth Int'l Co., Ltd. - Cino Group, all rights reserved. Due to Cino's continuing product improvement program, specifications and features herein are subject to change without notice. Cino is a registered trademark of PC Worth Int'l Co., Ltd. Any reproduction, duplication or other use of the contents of this catalog, in part or in full, without the prior permission of PC Worth Int'l Co., Ltd. is strictly forbidden.